

# Logo Placements

## 1561 Jacket CL 3

### Recommended logo placements

#### Heat seal & Embroidery


- 1 Left breast, 1 cm above pocket, maximum size 60x60 mm
- 3 Right breast, in line with placement 1, maximum size 60x60 mm
- 4 Right sleeve, top of logo 5 cm below shoulder seam, maximum size 120x100mm
- 6 Back, 2 cm below yoke seam, maximum size 180x280mm
- 23 Right breast, in line with placement 24, maximum size 120x100 mm
- 63 Back, 2 cm above end seam, maximum size 280x50 mm
- 62 Back, 13 cm below yoke seam maximum size 250x280 mm

#### Heat seal

- 24 Left breast pocket, top of logo in line with top of zipper, maximum size 80x100 mm

To maintain 3 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.


 Add  
 B after the placement and it will be below the (1B)  
 Y and it will be turned from bottom to top  
 Z after the placement and it will be turned from top to bottom



Maximum size of logo cm<sup>2</sup> to keep classification EN 20471

Size	cm <sup>2</sup>	cm
XS	200	14x14
S	800	28x28
M	1500	38x38
All other	2200	46x46



How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm<sup>2</sup> shall be tested in ISO 15025, Procedure A.

