



SAFETY DATA SHEET
2WORK FLOOR STRIPPER

Page: 1

Compilation date: 01/08/2008

Revision date: 11/05/2015

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 2WORK FLOOR STRIPPER

Product code: 2W04498

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: INTERACTION-CONNECT SA
54 BLVD NAPOLEON IER
L-2210 LUXEMBOURG

Tel: +33 93808248

Email: WWW.OPINFO.NET

1.4. Emergency telephone number

Emergency tel: NHS Direct 08454647

NHS24 0845242424

ROI 018092166

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314; STOT SE 3: H335

Most important adverse effects: Causes severe skin burns and eye damage. May cause respiratory irritation.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation.

Signal words: Danger

[cont...]

SAFETY DATA SHEET

2WORK FLOOR STRIPPER

Page: 2

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark



Precautionary statements: P102: Keep out of reach of children.

P282: Wear eye protection.

P280: Wear protective gloves.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P332+313: If skin irritation occurs: Get medical attention.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical attention.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314: Get medical attention if you feel unwell.

P362: Take off contaminated clothing and wash before reuse.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

3 - BUTOXYPROPAN - 2 - OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
225-878-4	005131-66-8	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	10-30%

2-AMINOETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
205-483-3	141-43-5	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

[cont...]

SAFETY DATA SHEET

2WORK FLOOR STRIPPER

Page: 3

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain.
The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel.
Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Neutralise with dilute hydrochloric acid.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Avoid the formation or spread of mists in the air.

[cont...]

SAFETY DATA SHEET

2WORK FLOOR STRIPPER

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Polyethylene.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-AMINOETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	7.6 mg/m ³	15 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type K: ammonia and derivatives (EN141).

Hand protection: Gloves (alkali-resistant). Viton gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Non-viscous

Boiling point/range°C: 100

Melting point/range°C: 0

Flammability limits %: lower: Not applicable.

upper: Not applicable.

Flash point°C: Not applicable.

Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable.

Vapour pressure: Not applicable.

Relative density: 1.0 - 1.05

pH: 11.6

VOC g/l: 160

[cont...]

SAFETY DATA SHEET

2WORK FLOOR STRIPPER

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

3 - BUTOXYPROPAN - 2 - OL

ORAL	RAT	LD50	2700	mg/kg
------	-----	------	------	-------

2-AMINOETHANOL

IVN	RAT	LD50	225	mg/kg
ORL	MUS	LD50	700	mg/kg
ORL	RAT	LD50	1720	mg/kg
SCU	RAT	LD50	1500	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain.
The vision may become blurred. May cause permanent damage.

[cont...]

SAFETY DATA SHEET

2WORK FLOOR STRIPPER

Page: 6

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

3 - BUTOXYPROPAN - 2 - OL

-	48H EC50	>1000	mg/l
GUPPIES	96H LC50	560-1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable. The surfactants contained in this preparation comply with the biodegradability criteria as laid down in regulation (EC) No.648/2004 on detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET
2WORK FLOOR STRIPPER

Page: 7

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.

Legend to abbreviations: PNEC = predicted no effect concentration

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

OPT = optical

INH = inhalation

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]