

## 40-6606.pdf

**Model #:** 40-6606  
**UPC:** 049448066063



360 degree horizontal laser line and 1 vertical line. Locking compensator protects inner mechanisms. Visual out-of-level indicator. Manual mode for use at any angle. 1/4"-20 tripod thread for use with most common tripods. Ideal for carpentry, tile, and more. 40-6606 INCLUDES > Laser, 2 "AA" alkaline batteries.

### PRODUCT DETAILS

- 360 degree horizontal laser line and 1 vertical line
- Locking compensator protects inner mechanisms
- Visual out-of-level indicator
- Manual mode for use at any angle
- 1/4"-20 tripod thread for use with most common tripods
- Ideal for carpentry, tile, and more

### SPECIFICATIONS

<b>Accuracy</b>	±3/16"/30'
<b>Battery Life</b>	12 hours continuous use
<b>Dimensions</b>	2.3" x 3.6" x 4.2"
<b>IP Protection Class</b>	IP 50
<b>Laser Classification</b>	Class II
<b>Laser Wavelength</b>	635nm±10nm (Red)
<b>Leveling Method</b>	Self-Leveling (Pendulum)
<b>Maximum Power Output</b>	≤1mW
<b>Power Supply</b>	2 "AA" alkaline batteries (included)
<b>Self-Leveling Range</b>	±5°
<b>Warranty</b>	2 Years
<b>Weight</b>	10.5 oz (without batteries)
<b>Working Range</b>	Up to 35'
<b>Working Temperature</b>	32° F to 104° F



## APPLICATION

The Johnson Level 40-6606 can be used for the following indoor applications; flooring, cabinetry, drop ceiling installation, wainscoting, carpentry, tiling, electrical boxes and switches, drywall track/stud wall installation, setting drainage slope



For additional information on Johnson products, please contact  
Customer Service at 888.953.8357 or [service@johnsonlevel.com](mailto:service@johnsonlevel.com)  
[www.johnsonlevel.com](http://www.johnsonlevel.com) | © Johnson Level & Tool Mfg. Co. Inc.