H2-R

Product Name: H2-R

Product Number: 700H2-R (A or B)

Rechargeable headlamp with 82 + 420 lumens, red LED and twist style focus

1 x 18650: 3.7V - 2600mAh - 9.62Wh - Lithium

ABS and aluminium

rechargeable battery

Twist style optical focus system

Required: 100V-240V, 50-60Hz

5W CREE XPG2-R4

7500K

Acrylic, optical

Top, red rubber



series

Description

Specifications

Housing Lens On/off switch

Battery type

- Light source Colour temperature (Kelvin) Focus Charger operating voltage Charger output Output 30 seconds (lumen) Run time (ca. hours) down to 1 lumen Run time (ca. hours/min.) down to 10% lumens Charging time (hours) Charging level indicator Beam distance (m) Beam width (cm) from 1 m distance Protection class Operating temperature range (Celsius) Charging port Charging port cover Cable for charger, ca. 1 m (supplied in box) Additional data
- 82 (low beam) / 420 (high beam) 16 (low beam) / 7 (high beam) 13.40 (low beam) / 4.10 (high beam) 6 1 x LED on battery compartment 60 (low beam) / 150 (high beam) 160 (flood) / 25 (spot) IP65 / III -5°C to +40°C Micro USB Rubber, black USB into charger, Micro USB into lamp

Required: DC5V - 1A max (USB connector)

47 g and 163 g incl. battery Ø3.3 (cylinder) / 4.5 x 6.7 x 5.2 (housing) 5703296700054 5703296710053 5703296720052 8513100000

Red LED: 8 lumens - 12 m beam distance

"PRO" design printed box
12.5 x 12 x 12.5 cm
430 g
6 (inner carton) / 36 (outer carton)
38 x 25.5 x 13.5 cm (inner carton)
41.3 x 39.5 x 53 cm (outer carton)
2.7 kg (inner carton) / 18.1 kg (outer carton)



Features

Packaging Description

Box size (ca.)

Box weight (ca.)

Carton quantity (pcs)

Carton size 6 pcs. (ca.)

Carton size 36 pcs. (ca.)

Carton weight (ca.)

General Information

Lamp dimensions (ca.)

EAN code inner carton

EAN code outer carton Harmonized standard code

EAN code box (1 pc)

Lamp weight (ca.)

Rechargeable, lightweight headlamp with red LED and twist style focus Charging indicator (1 x LED), red = charging / green = fully charged Switch mode main light: low - high - off Switch off at any stage by holding down switch 2 sec. Switch on again at same stage Battery compartment on back of the neck Red LED on back of battery compartment. Separate switch. Switch mode: on - off Cable in cold resistant PVC (down to -40 degrees C) Soft pad and high quality elastic strap (around and over head)

With EU or UK plug (A or B)



ELWIS

Elwis Lighting A/S Sandtoften 11, 2820 Gentofte, DK www.elwislighting.com - Tel. +45 70 20 10 24

Version 3a 08/2017 © Elwis Lighting 2017 All details without obligation