

Product information

18V Combi Drill BL LXT



Satisfying the professional's needs

DHP483ZJ

Capacity in Steel	13 mm
Capacity in Wood	36 mm
Chuck Capacity	1.5 - 13 mm
Capacity in Masonry	13 mm
Blows per Minute (Hi) - ipm	0 - 25,500 ipm
Blows per Minute (Lo) - ipm	0 - 7,500 ipm
No Load Speed (Hi)	0 - 1,700 rpm
No Load Speed (Lo)	0 - 500 rpm
Voltage	18 v
Torque Settings	20 + Drill
Battery Type	Lithium-ion
Vibration: Drilling	2.5 m/sec ²
Vibration: Hammer Drilling	10.0 m/sec ²
Vibration K factor	1.5 m/sec ²
Noise sound pressure	83 dB(A)
Noise sound power	94 dB(A)
Noise K factor	3 dB(A)
Body only machine	1
Net weight	1.6 kg
Max. Fastening Torque (Soft Joint)	23 Nm
Max. Fastening Torque (Hard Joint)	40 Nm



STANDARD EQUIPMENT: 821550-0 MAKPAC CONNECTOR CASE (TYPE 2), 837670-0 INNER TRAY

- Compact overall length of 176mm
- Electric brake
- 2 mechanical gears.
- Variable speed
- Forward/reverse rotation
- Twin LED job light
- Brushless motor
- Single sleeve keyless chuck allows for easy bit installation/removal by one hand.
- Ergonomically designed high comfort grip.
- Belt hook

Details correct as of: 13-3-2018

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makitauk.com