

Product information

18v LXT Impact Driver



Satisfying the professional's needs

DTD152Z

Voltage	18 v
Standard Bolt	M5-M16
High Tensile Bolt	M5-M12
Coarse thread (length)	22 - 125 mm
Max Fastening Torque	165 Nm
No Load Speed	0 - 2900 rpm
Battery Type	Lithium-ion
Vibration: Fastening Bolt	10.5 m/sec ²
Vibration K factor	1.5 m/sec ²
Noise sound pressure	93 dB(A)
Noise sound power	104 dB(A)
Noise K factor	3 dB(A)
Body only machine	1
Net weight	1.5 kg
Driving Shank	6.35mm (1/4") Hex
Machine Screw	M4-M8
Impacts per Minute	0 – 3,500 ipm



LITHIUM-ION

- Electric brake
- Variable speed control by trigger
- Forward/reverse rotation
- Twin LED job light
- Ergonomic soft grip
- Compact and lightweight design
- Equipped with Battery protection circuit: designed to protect the battery from damages due to overdischarge, high temperature or overload current.
- High rotation speed
- One-touch bit installation

Details correct as of: 16-6-2017

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makitauk.com