

Product information

35MM SDS-MAX AVT ROTARY HAMMER



Satisfying the professional's needs

HR3541FC

| | |
|----------------------------|------------------------|
| Impact energy | 5.7 J |
| Max in concrete | 35 mm |
| 3-function H, R, R/H | 1 |
| Max core diameter (TCT) | 90 mm |
| Impacts rate | 1650 - 3300 bpm |
| Vibration K factor | 1.5 m/sec ² |
| Input wattage | 850 w |
| Joblight | 1 |
| Net weight | 5.2 kg |
| No Load Speed | 315 - 630 rpm |
| Vibration: Drilling | 2.5 m/sec ² |
| Vibration: Chiselling | 9 m/sec ² |
| Vibration: Hammer Drilling | 11 m/sec ² |
| Noise sound pressure | 91 dB(A) |
| Noise K factor | 3 dB(A) |
| Noise sound power | 102 dB(A) |



STANDARD EQUIPMENT: Side handle, Depth stop, Bit grease, Carry case

- Torque limiter: The drill stops when the bit hits against reinforcements.
- Triple operation mode: Rotary only, hammer only and rotary hammer.
- Soft start
- Constant speed under load
- Double Insulation
- Anti vibration technology
- Built-in job light

Details correct as of: 20-6-2017

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makita.com