



Handling protection

ULTRANE 524



Protection of electronic device from ElectroStatic Discharge (ESD)

SPECIFIC ADVANTAGES



Protection of electronic device from ElectroStatic Discharge (ESD)

- Product specifically developed to dissipate electrostatic charges, to protect electronic device from ElectroStatic Discharge (ESD) in compliance with EN16350 (ATEX glove standard)



Comfort

- High comfort & Breathability : second skin effect, thin liner to ensure suppleness & flexibility



Suitable for touchscreen

- Can be used with touch devices & touch screen (thumb & index)



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting
- No risk of damage of pieces handled



Washability

- Washable 1 time at 40°C without any alteration on performances*.

EN388



2X20A

EN 16350



DEXTERITY
EN 420:
5/5

CAT.2



INDUSTRIES

- Automotive/mechanical industry
- Electronics
- Aeronautics industry
- White appliance

APPLICATIONS

- Electronic card & component handling
- Precision assembly
- Part assembly
- Precision work
- Electronic component assembly (displays, LEDs, etc.)
- Quality control



Handling protection

ULTRANE 524

LEGENDS

| | |
|-----------------------|----------------------------------------------|
| EN388 | MECHANICAL HAZARDS |
| | PERFORMANCE LEVELS (X = NOT TESTED) |
| 2 X 2 0 A | |
| 0-4 0-5 0-4 0-4 A-F P | |
| | Impact protection (optional) |
| | Cut resistance according to ISO 13997 |
| | Puncture resistance |
| | Tear resistance |
| | Blade cut resistance |
| | Abrasion resistance |
| EN 16350 | PROTECTION AGAINST STATIC ELECTRICITY |
| | |

PRODUCT DETAILS

| | |
|-----------------------------------------------------------------------------------------|------------------------------------------------|
| Interior finish | Seamless textile support with conductive fiber |
| Gauge | 18 |
| Exterior finish | Ventilated back |
| Material | Polyurethane foam |
| Cuff characteristic | Knitted Cuff |
| Colour.s | Grey |
| European sizes | 6 7 8 9 10 11 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 1.9E+7 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 2.1E+7 Ω |

LOGISTIC DETAILS

| | |
|-----------|-----------------------------------------------|
| Packaging | 1 pair/bag 12 pairs/bag 96 pairs/carton |
|-----------|-----------------------------------------------|

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/20/1089
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE